

VARIOUS ELECTRICAL ACCESSORIES (TRANSFORMERS, TIMERS, HUMIDISTAT, AIR QUALITY SENSOR)

CT-12/14 and CT-12/14R

Transformer



Safety isolating transformer 230V/12V - 50Hz.

Fuse protection.

CT-12/14R: incorporates adjustable timer (1-30 mins).

Electrical supply		Output voltage (V)	IP Protection	Class	Maximum power (V.A.)
Frequency (Hz)	Supply voltage (V)				
50	220-240	12	IP21	II (□)	14

LxAxH (mm): 130 x 43 x 82

HIG-2

Humidistat



Enables the automatic ON/OFF operation of an extract fan by monitoring the relative humidity level.

Adjustable pre-set RH level 40-90%.

Incorporates timer.

IP Protection	Class	Maximum current (A)	Operating temperature	Humidity adjustment
IP21	II (□)	*6 (2)**	0-40 °C	40-90%

* For resistant loads

** For inductive loads

LxAxH (mm): 130 x 43 x 82

SQA

Air quality sensor



Automatically switches the fan on when the quality of the ambient air deteriorates below an acceptable level due to fumes, odours, tobacco, smoke or dampness etc...

Adjustable run-on-timer facility which enables the fan to operate for a pre-selected time period after the air quality sensor has switched off.

Important: this sensor must not be used to detect combustible gases or fires and in connection with any safety alarm systems.

IP Protection	Class	Maximum current (A)	Operating temperature	Timing
IP21	II (□)	*6 (2)**	0-50 °C	1-25 min.

* For resistant loads

** For inductive loads

LxAxH (mm): 130 x 43 x 82

ZN 62

Timer



Timer habitat range products.

Starting up: 1 min.

Timing: 6 min.

Resistive load - 2.5 A

Inductive load - 1.6 A

LxAxH (mm): 32 x 10 x 20